



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

Property Versesses Versesses



DAVID W. TAYLOR NAVAL SHIP RESEARCH AND DEVELOPMENT CENTER



Bethesda, Maryland 20084

AN ITERATIVE SOLUTION PROCEDURE FOR CALCULATING POTENTIAL FLOW

Ву

Yu-Tai Lee and Francis Noblesse

Approved for Public Release: Distribution Unlimited


SHIP PERFORMANCE DEPARTMENT DEPARTMENTAL REPORT



September 1985

DTNSRDC/SPD-1155-01

MAJOR DTNSRDC ORGANIZATIONAL COMPONENTS



UNCLASSIFIED

उटता	HY ZI XKKI	SCATION	OF THE	DAGE

REPORT DOCUMENTATION PAGE								
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	1b. RESTRICTIVE MARKINGS							
28. SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION / AVAILABILITY OF REPORT						
2b. DECLASSIFICATION / DOWNGRADING SCHEDU	LΕ	i						
4. PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5. MONITORING ORGANIZATION REPORT NUMBER(S)						
DTNSRDC/SPD-1155-01								
6a. NAME OF PERFORMING ORGANIZATION David W. Taylor Naval Ship	6b OFFICE SYMBOL (If applicable)	78. NAME OF MONITORING ORGANIZATION						
R&D Center		 						
6c. ADDRESS (City, State, and ZIP Code)		7b. ADDRESS (City, State, and ZIP Code)						
Bethesda, MD 20084-5000								
84. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER						
8c ADDRESS (City, State, and ZIP Code)		10 SOURCE OF	FUNDING NUMBER					
		PROGRAM ELEMENT NO	PROJECT NO	TASK NO.	WORK UNIT ACCESSION NO			
		61152N		ZR0230101	1843-045			
11 TITLE (Include Security Classification) 12 PERSONAL AUTHOR(S)								
Yu-Tai I	ee and Francis							
13a TYPE OF REPORT 13b TIME COVERED DEPARTMENTAL FROM TO		14. DATE OF REPORT (Year, Month, Day) 15 PAGE COUNT 1985, June						
16 SUPPLEMENTARY NOTATION								
17 COSATI CODES		Continue on reverse if necessary and identify by block number)						
FIELD GROUP SUB-GROUP		POTENTIAL FLOW, INTEGRAL EQUATIONS . ITERATIVE SOLUTION PROCEDURE						
10 APSTRACT (Continue on content of content]	washeel						
The report presents the results of a numerical investigation of a novel recurrence relation for iteratively solving modified integral equations for calculating free-surface potential flow. Numerical results are presented for the simple case of wave radiation in the zero- and infinite-frequency limits.								
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT 21 ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED UNCLASSIFIED								
220 NAME OF RESPONSIBLE INDIVIDUAL Yu-Tai Lee, Francis Noblesse	226 TELEPHONE 202/227-18	(Include Area Code 356	22c OFFICE 9	YMBOL				

DD FORM 1473, 84 MAR

83 APR edition may be used until exhausted All other editions are obsolete

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

TABLE OF CONTENTS

	Pa	age .
LIST OF FIGURES		lii
ABSTRACT		1
ADMINISTRATIVE INFORMATION		1
INTRODUCTION		1
INTEGRAL EQUATIONS		2
FLOW ABOUT AN ELLIPSOID IN AN UNBOUNDED FLUID		5
FLOW ABOUT A SHIP FORM AT ZERO AND INFINITE FREQUENCY		7
CONCLUSION		7
REFERENCES		13
LIST OF FIGURES		
1 - Convergence of the Neumann Series (8) Associated With the Integral Equation (1) for Flow About An Ellipsoid		9
2 - Hull Form Used in Calculations Presented in Figures 3 and	14	10
3 - Convergence of the Recurrence Relation (9) Associated Wit		
Integral Equation (6) for Zero-Frequency Flow About a Type Ship Form		11
4 - Convergence of the Recurrence (10) Associated With the Integral Equation (7) for Infinite Frequency Flow About a		10
Typical Ship Form		12
	Accession For	
	NTIS GRA&I DTIC TAB Unannounced Justification_	2 00.
OTIC		
(COPY)	By	
iii "MAPECTED	Availability	Codes

nsail and/or Extends

ABSTRACT

The report presents the results of a numerical investigation of a novel recurrence relation for iteratively solving modified integral equations for calculating free-surface potential flow. Numerical results are presented for the simple case of wave radiation in the zero- and infinite-frequency limits.

ADMINISTRATIVE INFORMATION

This research was funded under the David W. Taylor Naval Ship Research and Development Center's Independent Research Program, Program Element 61152N, Task Area ZR0230101, and Work Unit 1843-045.

INTRODUCTION

Most of the numerical methods reported in the ship-hydrodynamics literature for calculating potential flow about ship-hull forms, whether free-surface effects are taken into account or are neglected as in the so-called double-hull approximation (in which the free surface is treated as a rigid wall), closely follow the pioneering method of Hess and Smith¹. Briefly, this well-known numerical method consists in determining the density of an auxiliary distribution of sources on the body surface, in the classical manner described by Kellogg², by numerically solving an integral equation. This integral equation is solved by approximating the surface of the body by an ensemble of planar panels and assuming a constant (uniform) source density within each panel. The integral equation is then approximated by a system of linear equations, which is solved by inverting the coefficient-matrix, so-called "matrix of influence coefficients".

A number of variations and extensions of the method of Hess and Smith have been proposed. In particular, alternative integral equations have been

formulated — by using an auxiliary distribution of normal dipoles (instead of sources as in the method of Hess and Smith) or by directly applying Green's third identity to the velocity potential and the fundamental source potential (Green function) — and solved numerically. Important improvements to the basic Hess and Smith method have recently been incorporated into the so-called higher-order panel method³, in which curved panels supporting linear-source and quadratic-dipole distributions are used.

An alternative approach for calculating potential flow about a body in an unbounded fluid, in which a modified integral equation for determining the velocity potential is solved iteratively, has been proposed^{4,5,6,7}. This alternative approach has also been extended to the calculation of free-surface potential flows^{8,9,10}. A main recommendation of this alternative approach is that the modified integral equations upon which the approach is based have regular kernels, whereas the traditional integral equations used in the previously-mentioned method; have singular kernels. Another potential advantage of the alternative approach resides in the use of an iterative solution procedure, which is well suited to the analysis of complex systems requiring a large number of panels⁶. This report presents the results of a limited numerical investigation of the novel recurrence relation proposed in Noblesse¹⁰. More precisely, this recurrence relation is studied here for the simple case of wave radiation in the zero- and infinite-frequency limits.

INTEGRAL EQUATIONS

This study considers potential flow due to translation or rotation of a rigid, nonlifting body through an incompressible and inviscid fluid. The surface of the body is denoted by S, and \hat{n} represents the unit normal vector to S pointing inside the body. Furthermore, \hat{x} (x, y, z) and $\hat{\xi}$ (ξ , η , ζ) represent the position vectors, with respect to a rectangular system of coordinates

attached to the moving body, of any two points on the body surface S. The coordinates \bar{x} and $\bar{\xi}$ are adimensional, with respect to some length characterizing the size of the body taken as reference. The velocity potential, ϕ say, of the flow likewise is adimensional, with the body characteristic length and some characteristic speed of its motion used as reference. The normal component of the fluid velocity at any point \bar{x} on the body surface, given by $\phi_n = \nabla \phi \cdot \bar{n}$, is equal to the normal component of the velocity of S at \bar{x} , and thus is known for all six fundamental motions of the body (translation and rotation about the x, y, z axes).

The Green function appropriate for an unbounded fluid is given by $4\pi G(\xi,x) = -1/r$ where $r = \left[(\xi-x)^2 + (\eta-y)^2 + (\zeta-z)^2 \right]^{1/2}$. Application of Green's third identity to the velocity potential $\phi(x)$ and the foregoing free-space Green function $G(\xi,x)$ yields the following classical integral equation for determining the potential $\phi(\xi)$ at any point ξ on S:

$$\phi(\vec{\xi})/2 = f(\vec{\xi}) + L(\vec{\xi}; \phi), \tag{1}$$

where $f(\vec{\xi})$ is the known (since ϕ_n is specified on S) potential defined as

$$f(\xi) = -\int_{S} G(\xi, x) \phi_{n}(x) da(x), \qquad (2)$$

and $L(\xi;\phi)$ represents the integral transform of ϕ defined as

$$L(\xi;\phi) = \int_{S} G_{n}(\xi,x)\phi(x)da(x). \tag{3}$$

In equations (2) and (3), da(x) represents the differential element of area of the surface S at the point x.

The previously-mentioned modified integral equation corresponding to the classical integral equation (1) takes the form^{5,6,7}

$$\phi(\vec{\xi}) = f(\vec{\xi}) + L'(\vec{\xi}; \phi), \tag{4}$$

where $f(\xi)$ is the known source potential given by equation (2) and $L'(\xi;\phi)$ is the integral transform of ϕ defined as

$$L'(\vec{\xi};\phi) = \int_{S} G_{n}(\vec{\xi},\vec{x}) [\phi(\vec{x}) - \phi(\vec{\xi})] da(\vec{x}).$$
 (5)

A noteworthy feature of the modified integral equation (4) is that the integrand $G_{\Pi}(\xi,x)[\phi(x)-\phi(\xi)]$ of the integral (5) remains finite as the "integration point" x approaches the "calculation point" ξ .

The radiation potential for a body intersecting a free surface must satisfy the free-surface boundary condition $\partial\phi/\partial z - (\omega^2 L/g) \phi = 0$ on the equilibrium plane of the free surface taken as the plane z=0 with the z axis pointing upward, where ω = radiant frequency of oscillatory motion of the body, L = body characteristic length and g = acceleration of gravity. In the zero-frequency limit $\omega^2 L/g = 0$ and the infinite-frequency limit $\omega^2 L/g = \infty$, the free-surface boundary condition takes the simple degenerate forms $\partial\phi/\partial z = 0$ and $\phi = 0$, respectively. The Green functions G^0 and G^∞ corresponding to these limiting cases are given by $4\pi G^0 = -1/r - 1/r'$ and $4\pi G^\infty = -1/r + 1/r'$, where $r = [(\xi-x)^2 + (\eta-y)^2 + (\zeta-z)^2]^{1/2}$ as was defined previously and $r' = [(\xi-x)^2 + (\eta-y)^2 + (\zeta+z)^2]^{1/2}$.

The modified integral equation, corresponding to equation (4), for the zero-frequency potential, ϕ^0 say, takes the form 1.

$$\phi^{0}(\vec{\xi}) = f^{0}(\vec{\xi}) + L^{0}(\vec{\xi}; \phi^{0}), \tag{6}$$

where the potentials $f^0(\xi)$ and $L^0(\xi;\phi^0)$ are defined as

$$f^{0}(\vec{\xi}) = -\int_{S} G^{0}(\vec{\xi}, \vec{x}) \phi^{0}_{n}(\vec{x}) da(\vec{x}),$$

$$L^{0}(\overline{\xi};\phi^{0}) = \int_{S} G^{0}_{n}(\overline{\xi},\overline{x}) \left[\phi^{0}(\overline{x}) - \phi^{0}(\overline{\xi})\right] da(\overline{x}).$$

The corresponding modified integral equation for the infinite-frequency potential, ϕ^{∞} say, takes the form 11

$$[1-w(\vec{\xi})]\phi^{\omega}(\vec{\xi}) = f^{\omega}(\vec{\xi}) + L^{\omega}(\vec{\xi};\phi^{\omega}), \tag{7}$$

where the potentials $f^{\infty}(\xi)$ and $L^{\infty}(\xi;\phi^{\infty})$ are defined as

$$f^{m}(\vec{\xi}) = -\int_{S} G^{m}(\vec{\xi}, \vec{x}) \phi^{m}_{n}(\vec{x}) da(\vec{x}),$$

$$L^{\infty}(\vec{\xi};\phi^{\infty}) = \int_{S} G^{\infty}_{n}(\vec{\xi},\vec{x}) \left[\phi^{\infty}(\vec{x}) - \phi^{\infty}(\vec{\xi})\right] da(\vec{x}),$$

and $w(\xi)$ is the waterplane integral defined as

$$2\pi w(\xi) = -\zeta \iint_{\sigma} [(\xi-x)^2 + (\eta-y)^2 + \zeta^2]^{-3/2} dxdy,$$

with σ = portion of the mean free-surface plane inside the body (w = 0 for a fully-submerged body). By expressing the integrand of the foregoing waterplane integral in the form $\partial(x-\xi)[(y-\eta)^2+\zeta^2]^{-1}[(x-\xi)^2+(y-\eta)^2+\zeta^2]^{-1/2}/\partial x$ and using Green's theorem, we may express the waterplane integral in the form of the equivalent waterline integral

$$2\pi w(\xi) = -\zeta \int_{C} (x-\xi)[(y-\eta)^{2}+\zeta^{2}]^{-1}[(x-\xi)^{2}+(y-\eta)^{2}+\zeta^{2}]^{-1/2}dy,$$

where c represents the intersection curve of the body surface S with the plane z = 0.

FLOW ABOUT AN ELLIPSOID IN AN UNBOUNDED FLUID

The practicality of solving the classical integral equation (1) by using an iterative solution procedure based on the Neumann series

$$\phi^{(n+1)}(\xi)/2 = f(\xi) + L(\xi;\phi^{(n)}), \qquad (8)$$

with n>0 and $\phi^{(0)} \equiv 0$, has been investigated numerically for the simple case of flow about an ellipsoid with major, intermediate and minor dimensions equal to

1, 0.15 and 0.1, respectively. Figure 1 depicts the relative errors associated with the nth approximations A₁₁(n) to the added-mass coefficients A₁₁ for all six fundamental motions of the ellipsoid (1 = 1 to 6). This figure shows that the Neumann series (8) converges fairly rapidly for all motions except for surge (translation in the direction of the major axis). This numerical result is in agreement with the theoretical result obtained in Noblesse and Triantafyllou⁷ for translatory motions of ellipsoids. In particular, it is proved in this study that the Neumann series (8) fails to converge for a needle-like spheroid in longitudinal translation. Figure 1 shows that the sixth and fourth iterations are essentially exact for sway and heave (translations in the directions of the intermediate and minor axes), respectively. Convergence is even faster for roll and pitch, for which three iterations are sufficient. Finally, five iterations are necessary for yaw.

The velocity potential $\psi(\xi)$ associated with the modified integral equation (4) and defined as

$$\psi(\overline{\xi}) = f^{2}(\overline{\xi})/[f(\overline{\xi})-L'(\overline{\xi};f)]$$

is proved in [7] to be exact for translatory motions of any ellipsoid. This theoretical result has been verified numerically for the ellipsoid considered in Figure 1. The potential $\psi(\xi)$ has also been verified numerically to be exact for rotational motions (roll, pitch and yaw). The accuracy of the calculated added mass coefficients for all six fundamental motions is within 0.4% by using approximately 400 panels. The above-defined potential $\psi(\xi)$ corresponds to the first approximation $\phi^{(1)}(\xi)$ in the sequence of iterative approximations $\phi^{(n)}(\xi)$ defined by the recurrence relation $\phi^{(n)}(\xi)$

$$\phi^{(n+1)}(\vec{\xi}) = \phi^{(n)}(\vec{\xi})f(\vec{\xi})/[\phi^{(n)}(\vec{\xi})-L'(\vec{\xi};\phi^{(n)})],$$

with n>0 and $\phi^{(0)}(\xi) \equiv f(\xi)$, associated with the modified integral equation (4). The practicality of using this recurrence relation for solving the

modified integral equations (6) and (7) is tested numerically in the following section for a typical hull form.

FLOW ABOUT A SHIP FORM AT ZERO AND INFINITE FREQUENCY

The foregoing recurrence relation for potential flow in an unbounded fluid takes the form

$$\phi_0^{(n+1)(\xi)} = \phi_0^{(n)}(\xi)f_0(\xi)/[\phi_0^{(n)}(\xi)-L_0(\xi;\phi_0^{(n)})]$$
(9)

for flow in the zero-frequency limit, corresponding to the modified integral equation (6). The corresponding recurrence relation associated with the modified integral equation (7) for flow in the infinite-frequency limit is

$$\phi_{\omega}(n+1)(\xi) = \phi_{\omega}(n)(\xi)f_{\omega}(\xi)/[\{1-w(\xi)\}\phi_{\omega}(n)(\xi)-L_{\omega}(\xi;\phi_{\omega}(n))\}]$$
(10)

The recurrence relations (9) and (10), with n > 0 and $\phi_0(0) = f_0$, $\phi_\infty(0) = f_\infty$, have been used for calculating the six added-mass coefficients A_{ii} for i = 1 to 6 in the zero- and infinite-frequency limits for the ship form depicted in Figure 2, with beam/length and draft/length ratios equal to 0.15 and 0.05, respectively. The relative errors associated with the n^{th} iterative approximations $A_{ii}^{(n)}$ to the added mass coefficients A_{ii} for all six fundamental motions of the ship (i = 1 to 6) are depicted in Figures 3 and 4 for flow in the zero- and infinite-frequency limits, respectively. These figures show that six to eight iterations are required.

CONCLUSION

The numerical results presented in this report indicate that the recurrence relations for free-surface flows corresponding to the recurrence

relations (9) and (10) for flow in the zero- and infinite-frequency limits may provide an efficient solution procedure compared to that associated with the classical integral equation as shown in Figure 1, especially for cases (hull form equiped with a bulb or a sonar dome, low Froude number, high frequency) for which a large number of panels is required. Further numerical study of these recurrence relations is required for ascertaining their practical usefulness.




Figure 1 - Convergence of the Neumann Series (8) Associated with the Integral Equation (1) for Flow About An Ellipsoid




Figure 2 - Hull Form Used in Calculations Presented in Figures 3 and 4




Figure 3 - Convergence of the Recurrence Relation (9) Associated with the Integral Equation (6) for Zero-Frequency Flow About a Typical Ship Form




Figure 4 - Convergence of the Recurrence Relation (10) Associated with the Integral Equation (7) for Infinite Frequency Flow About a Typical Ship Form

REFERENCES

- 1. Hess, J.L. and A.M.O. Smith, "Calculation of Potential Flow About Arbitrary Bodies," Progress Aeronautical Sciences, Vol. 8, pp. 1-138 (1966), Pergamon Press, New York, NY.
- 2. Kellogg, O.D., "Foundations of Potential Theory," (1929), Dover Publ., New York, NY.
- 3. Johnson, F.T., "A General Panel Method for the Analysis and Design of Arbitrary Configurations in Incompressible Flows," NASA Contractor Report 3079 (1980).
- 4. Landweber, L. and M. Macagno, "Irrotational Flow About Ship Forms,"

 Iowa Institute of Hydraulic Research Report No. 123, the Univ. of Iowa (1969).
- 5. Chow, S.K., A.Y. Hou and L. Landweber, "Hydrodynamic Forces and Moments Acting on a Body Emerging From an Infinite Plane," Phys. Fluids, Vol. 19, pp. 1439-1449 (1976).
- 6. Chow, S.K., Y.T. Lee and E.A. Owen, "An Integral-Equation/Singularity-Method Approach for 3-D Electromagnetic Field Determination in the End Region of a Turbine-Generator," IEEE Trans. on Magnetics, Vol. MAG-18, No. 2 (1982).
- 7. Noblesse, F. and G. Triantafyllou, "Explicit Approximations for Calculating Potential Flow About a Body," Journal of Ship Research, Vol. 27, pp. 1-12 (1983).
- 8. Noblesse, F., "A Slender-Ship Theory of Wave Resistance," Journal of Ship Research, Vol. 27, pp. 13-33 (1983).
- 9. Noblesse, F., "Integral Identities of Potential Theory of Radiation and Diffraction of Regular Water Waves by a Body," Journal of Engineering Mathematics, Vol. 17, pp. 1-12 (1983).

- 10. Noblesse, F., "On the Theory of Three-Dimensional Flow About a Ship Moving With Constant Speed in a Regular Sea," David Taylor Naval Ship Research and Development Center Report 83/007 (1983).
- 11. Noblesse, F., "On the Theory of Flow of Regular Water Waves About a Body," Department of Ocean Engg. Report 80-2, Massachusetts Institute of Technology (1980).

DTNSRDC ISSUES THREE TYPES OF REPORTS

- 1. DTNSRDC REPORTS, A FORMAL SERIES, CONTAIN INFORMATION OF PERMANENT TECHNICAL VALUE. THEY CARRY A CONSECUTIVE NUMERICAL IDENTIFICATION REGARDLESS OF THEIR CLASSIFICATION OR THE ORIGINATING DEPARTMENT.
- 2. DEPARTMENTAL REPORTS, A SEMIFORMAL SERIES, CONTAIN INFORMATION OF A PRELIMINARY, TEMPORARY, OR PROPRIETARY NATURE OR OF LIMITED INTEREST OR SIGNIFICANCE. THEY CARRY A DEPARTMENTAL ALPHANUMERICAL IDENTIFICATION.
- 3. TECHNICAL MEMORANDA, AN INFORMAL SERIES, CONTAIN TECHNICAL DOCUMENTATION OF LIMITED USE AND INTEREST. THEY ARE PRIMARILY WORKING PAPERS INTENDED FOR INTERNAL USE. THEY CARRY AN IDENTIFYING NUMBER WHICH INDICATES THEIR TYPE AND THE NUMERICAL CODE OF THE ORIGINATING DEPARTMENT. ANY DISTRIBUTION OUTSIDE DTNSRDC MUST BE APPROVED BY THE HEAD OF THE ORIGINATING DEPARTMENT ON A CASE-BY-CASE BASIS.

END

FILMED

11-85

DTIC